

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
10	HISTIC CRYAQUOLLS, NEARLY LEVEL								
		HISTIC CRYAQUOLLS	90	12-72	Frequent	Very limited	Very limited	Moderately rapid	Very low
11F	LEADVILLE GRAVELLY LOAM, 15 TO 55 PERCENT SLOPES								
		LEADVILLE	80	> 72	None	Very limited	Very limited	Slow	High
12C	LEAVITT LOAM, 0 TO 6 PERCENT SLOPES								
		LEAVITT	85	> 72	None	Not limited	Somewhat limited	Moderately slow	Medium
12D	LEAVITT LOAM, 6 TO 15 PERCENT SLOPES								
		LEAVITT	85	> 72	None	Somewhat limited	Very limited	Moderately slow	High
12F	LEAVITT LOAM, 15 TO 55 PERCENT SLOPES								
		LEAVITT	85	> 72	None	Very limited	Very limited	Moderately slow	Very high
13	MINE DUMPS								
		MINE DUMPS	100	> 72	None	Very limited	Very limited	Rapid	High
14C	MUGGINS SANDY LOAM, 0 TO 6 PERCENT SLOPES								
		MUGGINS	85	> 72	None	Somewhat limited	Somewhat limited	Slow	High
14D	MUGGINS SANDY LOAM, 6 TO 15 PERCENT SLOPES								
		MUGGINS	85	> 72	None	Somewhat limited	Very limited	Slow	Very high
14F	MUGGINS SANDY LOAM, 15 TO 35 PERCENT SLOPES								
		MUGGINS	85	> 72	None	Very limited	Very limited	Slow	Very high
15	PLACER DIGGINGS								
		PLACER DIGGINGS	100	> 72	None	Very limited	Very limited	Rapid	Low
16C	QUANDER COBBLY LOAM, 0 TO 6 PERCENT SLOPES								
		QUANDER	85	> 72	None	Somewhat limited	Very limited	Moderate	Low
16D	QUANDER COBBLY LOAM, 6 TO 15 PERCENT SLOPES								
		QUANDER	85	> 72	None	Somewhat limited	Very limited	Moderate	Medium
16E	QUANDER COBBLY LOAM, 15 TO 55 PERCENT SLOPES								
		QUANDER	85	> 72	None	Very limited	Very limited	Moderate	High
17F	QUANDER-YOUGA COMPLEX, 15 TO 55 PERCENT SLOPES								
		QUANDER	55	> 72	None	Very limited	Very limited	Moderate	High
		YOUGA	30	> 72	None	Very limited	Very limited	Moderate	High

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
18	ROCK OUTCROP-CRYOBOROLLS COMPLEX								
		ROCK OUTCROP	70	> 72	None	Very limited	Very limited	Very slow	Very high
		CRYOBOROLLS	20	> 72	None	Very limited	Very limited	Slow	Very high
19C	YOUNGA LOAM, 0 TO 6 PERCENT SLOPES								
		YOUNGA	85	> 72	None	Somewhat limited	Somewhat limited	Moderate	Low
19D	YOUNGA LOAM, 6 TO 15 PERCENT SLOPES								
		YOUNGA	85	> 72	None	Somewhat limited	Very limited	Moderate	Medium
19F	YOUNGA LOAM, 15 TO 45 PERCENT SLOPES								
		YOUNGA	85	> 72	None	Very limited	Very limited	Moderate	High
1D	ANVIK LOAM, 6 TO 15 PERCENT SLOPES								
		ANVIK	90	> 72	None	Somewhat limited	Very limited	Moderate	Medium
1F	ANVIK LOAM, 15 TO 35 PERCENT SLOPES								
		ANVIK	85	> 72	None	Very limited	Very limited	Moderate	High
20D	YOUNGA LOAM, THICK SURFACE, 6 TO 15 PERCENT SLOPES								
		YOUNGA	90	> 72	None	Somewhat limited	Very limited	Moderate	Medium
20F	YOUNGA LOAM, THICK SURFACE, 15 TO 50 PERCENT SLOPES								
		YOUNGA	90	> 72	None	Very limited	Very limited	Moderate	High
21D	YOVIMPA CLAY LOAM, 6 TO 15 PERCENT SLOPES								
		YOVIMPA	85	> 72	None	Very limited	Very limited	Slow	Very high
21F	YOVIMPA CLAY LOAM, 15 TO 45 PERCENT SLOPES								
		YOVIMPA	85	> 72	None	Very limited	Very limited	Slow	Very high
22	BORROW PITS								
		BORROW PITS	100	> 72	None	Not limited	Very limited	Rapid	Negligible
2F	BUCKLON LOAM, 15 TO 35 PERCENT SLOPES								
		BUCKLON	85	> 72	None	Very limited	Very limited	Moderately slow	Very high
3D	CIMARRON LOAM, 6 TO 15 PERCENT SLOPES								
		CIMARRON	85	> 72	None	Very limited	Very limited	Slow	Very high
3F	CIMARRON LOAM, 15 TO 35 PERCENT SLOPES								
		CIMARRON	85	> 72	None	Very limited	Very limited	Slow	Very high
4	CUMULIC CRYAQUOLLS, NEARLY LEVEL								
		CUMULIC CRYAQUOLLS	90	18-72	Frequent	Very limited	Very limited	Moderately rapid	Very low

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
5E	FRISCO-PEELER COMPLEX, 6 TO 25 PERCENT SLOPES								
		FRISCO	55	> 72	None	Very limited	Very limited	Moderate	Medium
		PEELER	35	> 72	None	Very limited	Very limited	Moderate	Medium
5F	FRISCO-PEELER COMPLEX, 25 TO 65 PERCENT SLOPES								
		FRISCO	60	> 72	None	Very limited	Very limited	Moderate	High
		PEELER	30	> 72	None	Very limited	Very limited	Moderate	High
6	GRAVEL PITS								
		GRAVEL PITS	100	> 72	None	Not limited	Very limited	Rapid	Negligible
7D	GRENADIER GRAVELLY LOAM, 6 TO 15 PERCENT SLOPES								
		GRENADIER	80	> 72	None	Somewhat limited	Very limited	Moderate	Medium
7F	GRENADIER GRAVELLY LOAM, 15 TO 55 PERCENT SLOPES								
		GRENADIER	80	> 72	None	Very limited	Very limited	Moderate	High
8B	HANDRAN GRAVELLY LOAM, 0 TO 3 PERCENT SLOPES								
		HANDRAN	85	> 72	None	Somewhat limited	Very limited	Moderate	Low
8D	HANDRAN GRAVELLY LOAM, 3 TO 15 PERCENT SLOPES								
		HANDRAN	90	> 72	None	Somewhat limited	Very limited	Moderate	Medium
9F	HANDRAN BOULDERY LOAM, 15 TO 55 PERCENT SLOPES								
		HANDRAN	95	> 72	None	Very limited	Very limited	Moderate	High